

Keyless Entry Products



9747E Wireless Keyless Entry System - Rolling code

Frequency 433.92MHz

- Back-lit keyboard for easy use in the dark
- Can control multiple doors with a separate code
- Includes: keypad, 9V battery, and mounting hardware
- With rolling security code

Modulation: AM

Weight: 165g

Dimensions: 55x165x20mm



379E Wireless Keyless Entry System with fingerprint sensor

Frequency 433.92MHz

- Rolling code technology
- Weatherproof, with cover
- Stores up to 10 different fingerprints

Receiver



7433E Three Channel Co-axial Universal Receiver

Billion Code

Frequency 433.92MHz

- Three independent channels (one can be set for normally closed operation)-computer (billion) code
- Optional Plug-in AC transformer terminal
- External co-axial antenna included
- 455mm color-coded wire leads for each channel provided
- Continuous contact closure
- Open/Close/stop function
- Potential free output

Type:

AM superregenerative

Memory:

Each channel accepts 4 computer codes, 1 DIP, switch code and 1 wireless keyless entry system code

Voltage:

18-35V AC or DC with automatic recognition

Range:

Approximately 45m

Output Control: Relay switches up to 5A

3-Year Warranty



8002E 2-Channel Receiver

Billion & Rolling Code

All Frequencies

- Two channels
- Accepts LiftMaster RF modules
- RF module not included
- External power connection
- Test button
- Potential free output
- Water resistant plastic housing IP55
- Antenna

Memory:

15 codes each channel: 13 computer codes, 1 DIP-switch code, and 1 wireless keyless entry system code

Voltage:

9 to 35V AC/DC

Relay:

6A/60V max

Range:

Approximately 45m

Please note: Order RF module separately

2-Year Warranty on Receiver



801221 RF module

Frequency 433.92MHz

- Superheterodyne ("Narrow-band")
- For LiftMaster remote controls
- Direct plug-in to 801702 or 8002E and to CB11, CB22, CB24

Modulation: AM